

QWS/GWS

Widescreen *IP68*

Waterproof Weighing Indicator



QWS/GWS

Widescreen *IP68* Waterproof Weighing Indicator




Features:

- Extra-large and wide LCD display 55mm height, with COOL WHITE LED backlight
- IP68 Waterproof, mist-proof and dustproof
- QWS with 304 stainless steel housing while GWS with plastic ABS housing
- Quick access to hold function, weight check High/Low/OK
- Selectable tare range or up to full range tare; Pre-tare
- Auto zero tracking; Sampling counting; Auto average unit weight
- Gross/Net indication; Low power indication and auto power off
- Up to 1/15,000 display resolution
- Kilogram (kg) and pound (lb) weighing modes
- Built-in RS-232

Option:


- QWS: Waterproof pressure relief valve – for longer lifespan by preventing possible pressure build-up
 - GWS: U shape stand selectable
 - Choose RS-485 or Wireless; Wireless distance up to 100M available; (SPP mode* supported)
 - Convenient foot switch for one of the following: Zero, or Tare, or Print
- * SPP mode: Standard Parallel Port mode



J: 334 x 254mm



K: 322 x 242mm



T: 400 x 300mm



D: 420 x 520mm



L: 460 x 600mm



F: 400 x 500mm
420 x 520mm

*More sizes are available



▲
QWS: Pressure Relief Valve



▲
GWS: Sleeve Connecting Stand (Standard); U Shape Stand (Option)



Operating Temperature: -10°C ~ 40°C (14°F ~ 104°F)

Power Source: AC 110V/230V (±15%) + 6V / 4.5Ah rechargeable battery

Dimensions: QWS 232 x 150 x 80mm; GWS 238 x 156 x 90mm

Display: LCD 6 digits, 55mm height, COOL WHITE LED backlight



EXCELL PRECISION CO., LTD.

6F., No.127, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel +886 2 8919 1000 Website www.excell-scale.com

Fax +886 2 8919 1177 E-mail sales@excell-scale.com