







## PA2

## General Features

- Bright LCD display with LED backlight
- Overload protection design
- Enclosed with adjustable feet, bubble level, dust cover, rechargeable battery and power cord
- Tare function
- Low battery and charging status indication

## Non-Approval Model Features

- Selectable weight units: kg, 100g, lb, oz (depends on the require)
- Money return calculation of a trade balance
- Up to 99 data accumulation and 25 recall
- Dual range model and 1/6,000 display resolution available

## OIML Approval Model Features

- 1/3,000 display resolution
- Selectable weight units: kg, 100g
- 24 pre-set currencies exchange rate used in European countries

Specifications				
Model	Capacit	ty Acc	uracy Res	olution
PA/PAI-3	3 kg	1 g	1/3,000	)
PA/PAI-6	6 kg	2 g	1/3,000	)
PA/PAI-15	15 kg	5 g	1/3,000	)
PA/PAI-30	30 kg	10 g	1/3,000	)
Pan Size (WxD) 29	0mm x 220mn	1		
Display LC	D, 5/5/6 digits	, 13/13/18 mm	i (Height), LED bac	cklight
Power Supply AC	AC 110V/220V (±10%) or DC 6V/4AH rechargeable battery			
Approval Certificate EC	EC approval II certificate no.: T6262 / TC6305			
Operation Temperature Non-approval model: 0°C ~ 40°C (32°F ~ 104°F)				
Approval model: -10°C ~ 40°C (14°F ~ 104°F)				





6F, No. 127, Lane 235, Baoqiao Rd., Xindian District, New Taipei City 23145, Taiwan

 $\succ$ pm-all@excell.com.tw



+886-2-8919-1000



(+) https://www.excell-scale.com



+886-2-8919-1177