

# SXC Counting Indicator

## Lithium Powered



**NEW**  
Product



Long Operation



Low Carbon



Lightweight



Fast Charging



EXCELL<sup>®</sup>  
Since 1979

*e-Accura*



Operational Safety



Power Saving  
Mode



Maintenance Free

### Feature

- Bright LCD displays (13, 13, 18 mm digit height) with LED backlight
- Enclosed with indicator dust cover, rechargeable battery and power cord
- Easy to set any specification and up to 1/15,000 display resolution
- 15 levels sampling speed available
- Weight and quantity accumulation available
- Tare and pre-tare functions
- Auto average unit weight and 10 sets presets unit weight functions
- 5 brightness setting selectable for LCD backlight
- Built-in power saving function to extend usage time



### Specification

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Display               | LCD 13, 13, 18 mm (Height);<br>LED backlight                  |
| Power                 | AC 100V~240V ( $\pm 10\%$ ) adapter +<br>18650 LI-Ion battery |
| Dimensions            | 256 x 170 x 90mm ( W x H x D)                                 |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F)                                     |



6F, No. 127, Lane 235, Baoqiao Rd., Xindian  
District, New Taipei City 23145, Taiwan



pm-all@excell.com.tw



+886-2-8919-1000



+886-2-8919-2209



<https://www.excell-scale.com>

