

SUB / SUB ^{Both IP68 & IP69 Rating} AirCharge

Conquering High Pressure, Defying High Temperature



SUB / SUB Aircharge

- High-Quality Food-Grade Stainless Steel 304 Material, the Top Choice for Agricultural, Livestock, and Seafood Processing
- Futuristic Streamlined Design, Lightweight and Portable. Integrated Bottom Design for Easy Cleaning
- Powered by Lithium Battery 18650, Aligning with Environmental and Social Trends
- Exclusive Energy-Saving Patent, Maximizing Performance with Single-cell Lithium 18650 Type
- Exclusive Power Protection Device, Eliminating Concerns of Overcharging & Overdischarging Risks
- Plastic Materials with UL 94 V0 Flammability Rating Standard Ensuring User Safety


IP68 Rating



- 6** Protection against dust & other solid particles
- 8** Withstand in the water to depth min. 1 meter for at least 1 hour

SUB/SUB AirCharge has passed the SGS international certification for IP68 testing. Through testing, SUB/SUB AirCharge can be submerged underwater at a depth of 1 meter for over 50 hours.

IP69 Rating



- 6** Protection against dust & other solid particles
- 9** Withstand high temperatures & high-pressure water jets

SUB/SUB AirCharge is the first and only weighing scale in Taiwan to achieve the IP69 protection rating through SGS international certification.



SUB AirCharge

SUBe AirCharge

Capacity	3 / 3 / 6 / 6 / 15 / 15 kg	3 / 3 / 6 / 6 / 15 / 15 kg
Division	0.5 / 1 / 1 / 2 / 2 / 5 g	0.5 / 1 / 1 / 2 / 2 / 5 g
Battery	Li-ion rechargeable battery DC 3.7V 3200mA (18650-1P)	Li-ion rechargeable battery DC 3.7V 3200mA (18650-1P)
Power	AC 100V ~ 240V (±10%) adapter with 12V / 1.5A (15W) output QI TX module	AC 100V ~ 240V (±10%) adapter with 12V / 1.5A (15W) output QI TX module
Display	LCD: 6 digits / 25mm (height) White LED backlight	LED: 6 digits / 21mm (height)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
Dimensions	196 x 100 x 275 mm (W x H x D)	196 x 100 x 275 mm (W x H x D)
Platter Size	195 x 170 mm	195 x 170 mm
Charging Pad Size	110 x 84 mm	110 x 84 mm



SUB

SUBe

Capacity	3 / 3 / 6 / 6 / 15 / 15 kg	3 / 3 / 6 / 6 / 15 / 15 kg
Division	0.5 / 1 / 1 / 2 / 2 / 5 g	0.5 / 1 / 1 / 2 / 2 / 5 g
Battery	Li-ion rechargeable battery pack DC 3.7V 3200mA (18650-1P)	Li-ion rechargeable battery pack DC 3.7V 3200mA (18650-1P)
Power	AC 100V ~ 240V (±10%) adapter 12V / 1.5A	AC 100V ~ 240V (±10%) adapter 12V / 1.5A
Display	LCD: 6 digits / 25mm (height) White LED backlight	LED: 6 digits / 21mm (height)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
Dimensions	196 x 100 x 275 mm (W x H x D)	196 x 100 x 275 mm (W x H x D)
Platter Size	195 x 170 mm	195 x 170 mm



EXCELL PRECISION CO., LTD.

6F, No. 127, Lane 235, Baoqiao Road, Xindian District,
New Taipei City, 23145, Taiwan

+886 2 8919 1000

E-mail: pm-all@excell.com.tw



EXCELL Web QR Code