



FM FMR

Mini Indicator



FM/FMR Mini Indicator

Features:

- Large LCD (digit height 25.4mm) display with LED backlight
- Kilogram (kg), pound (lb) and ton (T) weighing modes
- Auto zero tracking; Animal scale function; Data accumulation function
- Multi-range and multi-interval setting available
- Gravity value calibration
- Combination key for multi-functions
- Environmental filter setting for better performance
- High resolution switch function to display 10 times divisions
- Available in connecting with up to four 350-ohm load cells
- Capable of connecting with 6-wire load cells

Options:

- Rechargeable battery set (5pcs of DC 6V Ni-MH batteries in serial connection)
- Dry battery set (5pcs of 1.5V UM-3 dry battery)
- RS232/485 serial interface with RTC function (switched by jumper)

Specifications:

Power Source	Adaptor: AC 120V/230V(50~60Hz); DC 12V/1000mA or Ni-MH rechargeable battery set (Optional)
Display	LCD, 6 digits, height 25.4mm, LED backlight
Operating Temperature	0°C~40°C (32°F~104°F)
Approval Model	-10°C ~ 40°C (14°F ~ 104°F)
Dimensions	193 x 134 x 49.5 mm (W x H x D)



LED

LCD



e-Accura



6F, No. 127, Lane 235, Baoqiao Rd., Xindian District,
New Taipei City 23145, Taiwan



pm-all@excell.com.tw



+886-2-8919-1000



<https://www.excell-scale.com>



+886-2-8919-1177

