

ESW PLUS Series

True **IP68** Mastery, the Professional Choice



LED Dual
Display



Load-Carrying
Max. 30KG



Washable



Fast Sampling
Speed



Multiple
Power Choices



Wireless
Charging



Fast
Charging

FEATURES

- Achieves IP68 dust & waterproof certification through SGS
- Utilizes food-grade stainless steel 304, ideal for agricultural & seafood processing
- Features an ergonomic design with convenient side grooved handles for easy carrying
- Displays data clearly & legibly with large LED & LCD screens
- Offers multiple work modes with the option of dual-sided LED displays
- Ensures precision & efficiency with outstanding linear performance & high-speed sampling
- Supports a maximum weighing capacity of up to 30kg
- Meets international standards with OIML & NTEP certifications
- Adapts to various scenarios with a range of power supply option

SPECIFICATION



	ESW AirCharge	ESW Plus	ESW Plus Dry Battery
Capacity	3 / 3 / 6 / 6 / 15 / 15 / 30 / 30 kg	3 / 3 / 6 / 6 / 15 / 15 / 30 / 30 kg	3 / 3 / 6 / 6 / 15 / 15 / 30 / 30 kg
Division	0.5 / 1 / 1 / 2 / 2 / 5 / 5 / 10 g	0.5 / 1 / 1 / 2 / 2 / 5 / 5 / 10 g	0.5 / 1 / 1 / 2 / 2 / 5 / 5 / 10 g
Battery	Li-ion rechargeable battery pack DC 3.7V 6100mA (18650-2P)	Lead-acid rechargeable battery DC 6V / 4Ah	D battery 1.5V *4 cells (shipped without battery)
Power	AC 100V ~ 230V (±10%) adapter with 12V / 1.5A (15W) output Qi TX module	AC 100V ~ 230V (±10%) adapter with 12V / 1.5A output	
LCD Display	6 digits / 25mm (height) White LED backlight	6 digits / 25mm (height) White LED backlight	6 digits / 25mm (height) Green LED backlight
Operating Temperature	-10°C ~ 40°C (-14°F ~ 104°F)	-10°C ~ 40°C (-14°F ~ 104°F)	-10°C ~ 40°C (-14°F ~ 104°F)
Dimensions	240 x 120 x 280 mm (W x H x D)	240 x 120 x 280 mm (W x H x D)	240 x 120 x 280 mm (W x H x D)
Platter Size	235 x 200 mm	235 x 200 mm	235 x 200 mm



	ESW-E AirCharge	ESW-E Plus
Capacity	3 / 3 / 6 / 6 / 15 / 15 / 30 / 30 kg	3 / 3 / 6 / 6 / 15 / 15 / 30 / 30 kg
Division	0.5 / 1 / 1 / 2 / 2 / 5 / 5 / 10 g	0.5 / 1 / 1 / 2 / 2 / 5 / 5 / 10 g
Battery	Li-ion rechargeable battery pack DC 3.7V 6100mA (18650-2P)	Lead-acid rechargeable battery DC 6V / 4Ah
Power	AC 100V ~ 230V (±10%) adapter with 12V / 1.5A (15W) output Qi TX module	AC 100V ~ 230V (±10%) adapter with 12V / 1.5A output
LED Display	6 digits / 15mm (height)	6 digits / 15mm (height)
Operating Temperature	-10°C ~ 40°C (-14°F ~ 104°F)	-10°C ~ 40°C (-14°F ~ 104°F)
Dimensions	240 x 120 x 280 mm (W x H x D)	240 x 120 x 280 mm (W x H x D)
Platter Size	235 x 200 mm	235 x 200 mm



EXCELL PRECISION CO., LTD.

6F, No. 127, Lane 235, Baoqiao Road, Xindian District,
New Taipei City, 23145, Taiwan

+886 2 8919 1000

E-mail: pm-all@excell.com.tw



EXCELL Web QR Code